MTC Mk2

TALK OUT:
Talkback signal

FOOTSWITCH:
Latching or momentary foot switch for Talkback

CUE OUT:
When CUE MIX is activated, only the signal from IN C/CUE MIX and the talkback signal (Unity Gain). Phonitor Matrix and monitoring modes are deactivated.

SUB OUT:
Mono summed output with full frequency range.

Mono:
Connect mono sources to the left channel.

IN C
or
CUE MIX (input for artist headphone mix).

Loudspeakers

Sources

Device panel labels

MAINS INPUT

POWER

⚠ CAUTION
RISK OF ELECTRIC SHOCK
DO NOT OPEN

ATTENTION
RISQUE DE CHOC ÉLECTRIQUE
NE PAS OUVRIR ⚠

CE

~90 V AC/~250 V AC, 50 Hz/60 Hz, P max. 15 W
Fuse (internal): T 1 A L 250V

UK CA

WARNING
TO REDUCE RISK OF FIRE OR ELECTRIC SHOCK DO NOT EXPOSE THIS UNIT TO RAIN OR MOISTURE.

AUDIO CONNECTORS
XLRs & TRS Jacks: Balanced
XLRs: Pin 2 = (+)
Use Mono Jacks for unbal. operation
RCA: Unbal. 0 dBu

spl

MTC Mk2

Serial No.

Made in Germany

TALK OUT | CUE OUT | SUB OUT | SP OUT 3 | SPEAKER OUT 2 | SPEAKER OUT 1 | METER OUT | IN D | IN C | IN B | IN A

FOOTSWITCH | CUE OUT | SUB OUT | SP OUT 3 | SPEAKER OUT 2 | SPEAKER OUT 1 | METER OUT | IN D | IN C | IN B | IN A

Mono

CUE MIX